



## WMO

### Wall-Mount Multi-band Omni Antenna

#### Features

- ◆ Ideal for outdoor applications
- ◆ Pentaband Cellular, GSM and 3G operation
- ◆ Comes with wall-mount bracket
- ◆ 5M cable pre-installed

#### Specifications

Frequency range	824-960 / 1710-2170 MHz
Gain	2.14 dBi
Polarisation	Linear - Vertical
VSWR	<2:1
Impedance	50 Ohm
Power rating	10W
Cable/Connector	5M RG58 and SMA-Male
Colour Finish	White
Material	Sheath - Fibreglass, Cap - Polycarbonate
Operating Temperature	-30 to + 80 degrees C
Dimensions	250 mm x 25 mm (hxd) + bracket

#### Popular Ordering Options

FWMO35193-SM-5K	WMO with 5M RG58 and SMA-Male
-----------------	-------------------------------

Specifications subject to change without notice.

5 Little Balmer  
Buckingham Industrial Park  
Buckingham  
MK18 1TF  
UK

Tel: +44 (0)1280 824055  
Fax: +44 (0)1280 817179  
Email: sales@ead-ltd.com  
Web: www.ead-ltd.com

**EAD**   
embedded antenna design ltd  
*Delivering Antenna Innovation*